



BONA TRAFFIC ANTI SLIP

Product Description

Features

Bona Traffic Anti Slip is a 100% polyurethane 2-component waterborne finish offering exceptional durability and protection for wooden floors. It has all of the features of Bona Traffic but with the additional benefit of being formulated to meet the highest Standards for slip resistance in workplaces and other situations with an increased risk of wet spills. With its higher friction, **Bona Traffic Anti Slip** is an ideal choice for stairs, nurseries, kitchens and similar locations

- Superb wear and chemical resistance
- High scuff mark resistance
- Excellent adhesion properties
- Non-yellowing
- Classified R10 according to DIN 51 130.

Technical Data

Type of finish:	2-comp. waterborne 100% polyurethane finish
Solids content:	Approx. 33%
VOC:	90 g/litre (incl. hardener)
Resistance to wear:	Approx. 2.5 mg/100 revolutions (SIS 923509)
Sheen (at 60°):	approx. 25
Mixing ratio:	1 part Traffic Hardener to 10 parts Traffic
Pot life:	5 hours at 20°C
Drying time:	3-4 hours at 20°C/60% R.H.
Application tools:	Bona Roller
Application rate:	8-10 m ² /litre (120-100g/m ²) per coat
Safety	Finish: Unclassified Hardener: Classified (see Safety Data Sheet)
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size (incl. Hardener):	3 x 4.95 litres (36 boxes per pallet)

Bona[®]