

SAFETY DATA SHEET



Carl's Oil 45

1. Identification of the preparation and of the company

Product name and/or code : Carl's Oil 45
Manufacturer : BonaKemi AB
Box 210 74
SE-200 21 MALMÖ
SWEDEN
+46-(0)40-38 55 00
Product use : Oil for treatment of wooden floors

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

| Chemical name* | CAS number | % | EC number | Classification |
|---|------------|----------|-----------|---|
| Naphta (petroleum), hydrogen treated heavy | 64742-48-9 | 25 - 50 | 265-150-3 | R10 Xn; R65 R66, R67 |
| Alkanes, C9-12-iso- | 90622-57-4 | 25 - 50 | 292-459-0 | Xn; R65 R66 R53 |
| Naphta (petroleum), hydrodesulfurized heavy | 64742-82-1 | 2.5 - 10 | 265-185-4 | R10 Xn; R65 R66, R67 |
| 2-Butanone, oxime | 96-29-7 | 0 - 1 | 202-496-6 | N; R51/53 Carc. Cat. 3; R40 Xn; R21 Xi; R41 R43 |
| See section 16 for the full text of the R-phrases declared above | | | | |

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10
R66, R67
R52/53

Physical/chemical hazards : Flammable.

Human health hazards : Repeated exposure may cause skin dryness or cracking.
Vapors may cause drowsiness and dizziness.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Additional warning phrases : Contains (2-Butanone, oxime). May produce an allergic reaction.

4. First aid measures

First aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in area where this material is

7. Handling and storage

handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Storage

: Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from: oxidizing agents, strong alkalis, strong acids.

No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains..

Specific uses

: Risk of self-ignition. Contaminated equipment for cleaning, cloths, rags, dust from sanding etc. can cause self-ignition. All cloths etc. must be put into water, sealed containers or be burnt.

8. Exposure controls/personal protection

Engineering measures : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Occupational exposure limits : Not available.

Personal protective equipment

Respiratory system : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Skin and body : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

Hands

Gloves : For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

| | |
|-------------------------|---------------------------------------|
| Physical state | : Liquid. |
| Color | : Brown. |
| Flash point | : Closed cup: 36°C (96.8°F). |
| Viscosity | : Kinematic: 9 cSt |
| Relative density | : 0.85 (Water = 1) |
| Solubility | : Insoluble in cold water, hot water. |

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains (2-Butanone, oxime). May produce an allergic reaction.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 2 and 15 for details.

Ecotoxicity data

| <u>Product/ingredient name</u> | <u>Species</u> | <u>Period</u> | <u>Result</u> |
|---|-----------------|---------------|---------------|
| Naphta (petroleum), hydrodesulfurized heavy 2-Butanone, oxime | Fish (LC50) | 72 hour/hours | 1 to 100 mg/l |
| | Bacteria (EC50) | 17 hour/hours | 281 mg/l |
| | Fish (LC50) | 96 hour/hours | 760 mg/l |
| | Daphnia (EC50) | 48 hour/hours | >500 mg/l |
| | Algae (EC50) | 72 hour/hours | 83 mg/l |

Ecological information

Persistence/degradability

| <u>Product/ingredient name</u> | <u>Aquatic half-life</u> | <u>Photolysis</u> | <u>Biodegradability</u> |
|--------------------------------|--------------------------|-------------------|-------------------------|
|--------------------------------|--------------------------|-------------------|-------------------------|

12. Ecological information

| | | | |
|--|---|---|------------------|
| Naphta (petroleum), hydrogen treated heavy | - | - | Readily |
| Alkanes, C9-12-iso-Naphta (petroleum), hydrodesulfurized heavy | - | - | Inherent Readily |
| 2-Butanone, oxime | - | - | Inherent |

Bioaccumulative potential

| <u>Product/ingredient name</u> | <u>LogP_{ow}</u> | <u>BCF</u> | <u>Potential</u> |
|---|--------------------------|------------|------------------|
| Naphta (petroleum), hydrodesulfurized heavy | 2 to 7 | - | high |
| 2-Butanone, oxime | 0.59 | - | low |

13. Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Yes.

14. Transport information

Transport within user's premises always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Land - road/railway

| | |
|-------------------------|---------|
| UN number | : 1263 |
| Transport document name | : PAINT |
| Special provision 640 | : E |
| ADR/RID Class | : 3 |
| Packing group | : III |
| ADR/RID Label | : |



Sea

| | |
|----------------------|------------------|
| UN number | : 1263 |
| Proper shipping name | : PAINT |
| Special provisions | : Not available. |
| IMDG Class | : 3 |
| Packing group | : III |
| IMDG Label | : |



| | |
|---------------------------|-----------|
| Marine pollutant | : No. |
| Emergency schedules (EmS) | : F-E,S-E |

Date of issue : 2006-05-23.

Page: 5/7

14. Transport information

Air

| | |
|--------------------------|------------------|
| UN number | : 1263 |
| Proper shipping name | : PAINT |
| Special provisions | : Not available. |
| ICAO/IATA Classification | : 3 |
| Packing group | : III |

The "viscosity exemption" provisions do not apply to air transport.

ICAO/IATA label :



Inland waterways

| | |
|----------------------|-----|
| Proper shipping name | : - |
| Packing group | : - |

15. Regulatory information

| | |
|-----------------------------------|---|
| EU regulations | : The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows: |
| Risk phrases | : R10- Flammable. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapors may cause drowsiness and dizziness. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| Safety phrases | : S2- Keep out of the reach of children. S24- Avoid contact with skin. S60- This material and its container must be disposed of as hazardous waste. S62- If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. |
| Additional warning phrases | : Contains (2-Butanone, oxime). May produce an allergic reaction. |

16. Other information

| | |
|--|---|
| CEPE Classification | : 1 |
| Full text of R-phrases referred to in sections 2 and 3 - Europe | : R10- Flammable. R40- Limited evidence of a carcinogenic effect. R21- Harmful in contact with skin. R65- Harmful: may cause lung damage if swallowed. R41- Risk of serious damage to eyes. R43- May cause sensitization by skin contact. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapors may cause drowsiness and dizziness. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R53- May cause long-term adverse effects in the aquatic environment. |

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

| | |
|----------------------|---------------|
| Date of issue | : 2006-05-23. |
| Version | : 1 |

[Notice to reader](#)

Date of issue : 2006-05-23.

Page: 6/7

16. Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.