



CARL'S HARD WAX OIL REFRESHER

Sitework

Preparation

Clean the floor thoroughly using Carl's Cleaner and allow the surface to dry properly. Where Carl's Hard Wax Oil has been recently applied the surface must be allowed to dry for 1 week prior to treatment with Carl's Hard Wax Oil Refresher.

Maintenance of existing surfaces:

Apply a thin coat of Carl's Hard Wax Oil Refresher across the floor using a lint free cloth or similar applicator. Apply along the grain where possible. Alternatively on larger floors spread using a white buffing pad. Leave the surface to dry for approx. 2 hours. If a glossier surface desired then polish, using either a soft cloth or a buffing machine with a white pad, until an even uniform silkmatt appearance is achieved across the whole floor.

Removal of wear marks / persistent stains:

Apply Carl's Hard Wax Oil Refresher to the affected areas and rub it using a cloth. Leave to dry for approx 2 hours. If required, lightly polish the treated areas afterwards to even out the gloss level with the rest of the floor. For heavy stains it is possible to use a Scotchbrite pad or the centre from a red pad to clean/prepare the surface.

Application rate

Ca. 1 litre/100 m² depending upon the application

Cleaning

Tools should be cleaned in White Spirit immediately after application.

Shelf life

5 years, from the date of production, in unopened original container.

Storage/transport/disposal

Store frost free in a cool, well ventilated area away from incompatible materials and ignition sources. Wastes and emptied containers should be handled in accordance with local regulations.

Fire risk/flash point

Flammable / 27°C.

R-10 Flammable

S-51 Use only in well ventilated areas